

STRIP 60 Led/m CRI>90 3 SDCM IP65



100mm

8mm

5000mm



DESCRIPTION

- 5 meter flexible strip, 60 led/m. Resin protection. 100mm divisible, dimmable.
- 3M biadhesive tape on the back.

TECHNICAL SPECIFICATIONS

Power	Nr. LED	Type LED	B. angle	CRI	CCT	Lm*	Lm/m*	Order code	
24W 4,8 W/m	300 60 led/m	2835 Entity	120°	>90	WW	2700K	1890	378	E40R-0000-L270
						3000K	1890	378	E40R-0000-L300
					NW	4000K	2025	405	E40R-0000-L400
					CW	6000K	2160	432	E40R-0000-L600
working temperature (t.amb.)				-30+40°C	protection rating		IP65		
max n° of reels in series				1 (5m)	adhesive tape on the back		3M		
dissipation required				NO					

Annotation: all datas are characterized at 25°C ambient temperature * nominal values ±10%

PACKAGING



- strip 5 meters in reel
- antistatic bag 24x26 cm
- identification label on bag

Legal note : ECE Srl is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing ECE Srl products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such ECE Srl products could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that ECE Srl products are used within specified operating ranges as set forth in the most recent ECE Srl products specifications. The products described in this document are subject to the foreign exchange and foreign trade laws. The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by ECE Srl for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of ECE Srl or others. The information contained herein is subject to change without notice.